



LED Outdoor Lights



IN WALL OUTDOOR LED LIGHTS

Introducing the new generation in outdoor lighting. Tec-Led's recessed LED waterproof in-wall lights provide soft yet effective spot lighting to outdoor areas such as pathways, patios, walkways and driveways. Available in either circular or square fitting, these lights are easily retro fitted to existing structures, drawing economical power.

SPECIFICATIONS



(Also available in silver finish)



(Also available in white finish)





| Code | LOWLR3WWW | LOWLS3WWW | LOWLT1WWW | LOWLH3WWW |
|------------------------|---------------------------------|-------------------------------|---------------------------------------|--------------------------------------|
| Description | Circular recessed outdoor light | Square recessed outdoor light | Circular small recessed outdoor light | Circular Halo recessed outdoor light |
| Power | 3W | 3W | 1W | 3W |
| Lumens | 67 | 67 | 51 | 40 |
| Material | 6063 aluminium | 6063 aluminium | 316 Stainless steel | Aluminium |
| Dimensions (H x W x D) | 75mm Ø x 70mm | 75mm x 75mm x 70mm | 20mm Ø x 54mm | 60mm Ø x 35mm |
| Hole size mm | 67mm Ø | 67mm Ø | 26mm Ø | 35mm Ø |
| Rating | IP65 | IP65 | IP66 | IP67 |
| Input | DC700mA | DC700mA | DC350mA | DC350mA |
| Service life | 40,000 hours | 40,000 hours | 40,000 hours | 40,000 hours |
| Colour temperature | Warm white 3000K | Warm white 3000K | Warm white 3000K | Warm white 3000K |
| Beam angle | 40° | 40° | 45° | 360° |
| Chip | CREE XPE | CREE XPE | CREE XPE | CREE XPE |

ON WALL OUTDOOR LED LIGHTS

Tec-Led Lighting's extensive range of on-wall lights provide outdoor lighting solutions whilst being an energy efficient outdoor lighting option. These decorative and functional light fittings are designed to give illumination to outdoor areas such as walls and exterior features of housing spaces.

SPECIFICATIONS



| Code | LOWLUD2x7WWW/DL | LOWLD2x7WWW/DL | LOWLW1WWW | LOWLB2WWW |
|------------------------|---------------------------------------|---------------------------------------|---|---|
| Description | Tubular surface mounted outdoor light | Tubular surface mounted outdoor light | Vertical square surface mounted outdoor light | Round directional surface mounted outdoor light |
| Power | 2 x 6W | 6W | 1.2W | 2.2W |
| Lumens | 760 | 380 | 70 | 70 |
| Material | Stainless Steel 316 | Stainless Steel 316 | Aluminium | Aluminium |
| Dimensions (H x W x D) | 144mm x 91mm x 62mm | 91mm x 82.5mm x 62mm | 80mm x 75mm x 19mm | 68mm Ø x 26.8mm |
| Rating | IP65 | IP65 | IP54 | IP54 |
| Input | 240VAC | 240VAC | DC350mA | DC700mA |
| Service life | 30,000 hours | 30,000 hours | 30,000 hours | 30,000 hours |
| Colour temperature | 2700K/600K | 2700K/600K | 3000K | 3000K |
| Beam angle | 60° | 60° | 120° | 120° |
| Chip | EPISTAR | EPISTAR | OSRAM | CREE |

IN GROUND OUTDOOR LED LIGHTS

Tec-Led Lighting's vast range of LED in-ground lights all utilise 24v low energy technology, enabling them to offer a greatly enhanced lamp life and power saving whilst meeting all outdoor lighting requirements. The sleek and attractive aluminium or stainless steel housings guarantee a fitting with efficient heat dissipation and corrosion resistance properties. These lights are perfect to highlight any outdoor features, both residential and commercial, worth shining a light on!

SPECIFICATIONS



| Code | LIG5WWW/DL24V | LIGR4WWW/DL | LIGRS9WWW/DL | LIGRL9WWW/DL | LIGSQ9WWW/DL |
|------------------------|---|---|---|---|--|
| Description | Circular recessed in ground outdoor LED light | Circular recessed in ground outdoor LED light | Circular recessed in ground outdoor LED light | Circular recessed in ground outdoor LED light | Square recessed adjustable in ground outdoor LED light |
| Power | 5W | 4W | 9W | 9W | 9W |
| Lumens | Warm White = 160 Daylight = 200 | 168/200 | 350 / 400 | Warm White = 724 Daylight = 850 | 330 / 380 |
| Material | 316 Stainless steel | Alumin. or 316 S/steel | 316 Stainless steel | 316 Stainless steel | 316 Stainless steel |
| Dimensions (H x W x D) | 48mm diam. x 86mm | 65mm Ø x 145mm | 90mm Ø x 107mm | 186mm Ø. x 98mm | 130mm x 130mm x 130mm |
| Hole size mm | 44mm Ø | 62mm Ø | 83mm Ø | 195mm Ø | 116mm x 116mm |
| Rating | IP67 | IP67 | IP68 | IP67 | IP67 |
| Input | 24VDC | 24VDC | 24VDC | 24VDC | 24VDC |
| Service life | 40,000 hours | 40,000 hours | 40,000 hours | 40,000 hours | 40,000 hours |
| Colour temp. | 2700K - 4500K | 3000K - 5500K | 3000K - 5500K | 3000K - 5500K | 3000K - 5500K |
| Beam angle | 15°, 30° | 25°, 40°, 60° | 15°, 30°, 40°, 60° | 15°, 30° | 15°, 40°, 60° |
| Chip | EPISTAR | CREE | CREE | CREE | CREE |

ABOVE GROUND OUTDOOR LED LIGHTS

Our diverse range of LED above-ground lights offer power saving and a significantly enhanced service life. The stainless steel or aluminium housings ensure a fitting with corrosion resistant properties and efficient heat dissipation, whilst catering to all outdoor requirements. These above-ground lights are the perfect solution for framing outdoor features and transforming outdoor spaces.

SPECIFICATIONS



(Also available in silver)

| Code | LOSL3WWWDL24V | LISL9WWWDL24V | LASLSS6WWW/DL | LASLLS6WWW/DL | LASLSB6WWW/DL | LASLLB6WWW/DL |
|------------------------|--|--|--|--|--|--|
| Description | 3W Spotlight | 9W Spotlight | 6W Spotlight | 6W Spotlight | 6W Spotlight | 6W Spotlight |
| Power | 1 x 3W | 3 x 3W | 6W | 6W | 6W | 6W |
| Lumens | Warm White = 50 Daylight = 60 | Warm White = 400 Daylight = 425 | Warm White = 310 Daylight = 370 | Warm White = 310 Daylight = 370 | Warm White = 310 Daylight = 370 | Warm White = 310 Daylight = 370 |
| Material | Aluminium | Aluminium | Stainless steel | Stainless steel | Aluminium | Aluminium |
| Dimensions (H x W x D) | 42mm Ø x 85mm x 60mm | 83mm Ø x 126mm x 300mm stalk | 76mm x 62mm Ø x 290mm stalk | 76mm x 62mm Ø x 486mm stalk | 76mm x 62mm Ø x 290mm stalk | 76mm x 62mm Ø x 486mm stalk |
| Rating | IP65 | IP65 | IP67 | IP67 | IP67 | IP67 |
| Input | 24VDC | 24VDC | 12VDC | 12VDC | 12VDC | 12VDC |
| Service life | 40,000 hours | 40,000 hours | 30,000 hours | 30,000 hours | 30,000 hours | 30,000 hours |
| Colour temp. | Warm white: 2700K, Day Light: 5500K | Warm white: 2700K, Day Light: 5500K | Warm white: 3000K, Day Light: 5500K | Warm white: 3000K, Day Light: 5500K | Warm white: 3000K, Day Light: 5500K | Warm white: 3000K, Day Light: 5500K |
| Beam angle | 40° | 60° | 60° | 60° | 60° | 60° |
| Chip | CREE | CREE | EPISTAR | EPISTAR | EPISTAR | EPISTAR |

LED OUTDOOR STRIP LIGHTING

Waterproof Flat Flex on Aluminium Bar

Flat Flex LED represents a versatile, energy saving and aesthetically successful lighting option in a myriad of applications for the professional commercial lighting specifier. It can be installed in the smallest of openings and yet still provide a range of tonal values to suit all ambiances. Any of our wide range of LED strip lighting can be converted into an outdoor IP65 rated fitting. The waterproof Flat Flex is perfect for outdoor stair lighting, highlighting water features and can even be used to frame pools. For further specifications regarding these LEDs please see our Flat Flex brochure



24V Snake Light

Providing a continuous glow with invisible light points and high brightness, the Snake light is especially suited for architectural illumination, both indoors and out. LEDs are encased in a robust PVC sheath, able to withstand foot traffic and the elements.



SPECIFICATIONS - Snake Light

| | | | |
|-----------------------|-------------------|---------------------------------|--|
| Code | LSNKL2700-6500RGB | Minimum cutting length | 100mm |
| LED Type | SMD 5050 tri-chip | Maximum connection | 10m |
| Material | PVC | IP Rating:* | IP68 |
| Working Voltage | DC24V | Transverse min bending diameter | 12cm |
| Rated power/m | 12W | Accessories | Front connector Middle connector End cap Aluminium U- channel |
| Lumens per metre | (Warm white) 330 | | |
| Distance between LEDs | 1.67cm | | |

www.tec-ledlighting.com.au



TEC-led lighting Pty Ltd

Unit 9 / 7-9 Kent Road, Mascot NSW 2020

Telephone: (02) 9317 4177 Facsimile: (02) 9317 3544

Email: sales@tec-ledlighting.com.au