

## LED Mini Downlights

TecLed offers a wide range of LED mini low glare downlights specifically designed for installation in cabinets, display shelving and anywhere else where a slim profile recessed downlight is required.

These downlights may be retrofitted to existing indoor cabinetry and provide an economical low voltage solution.



TL5002-3W  
Dimmable



TL-D0307



TL-D0302  
Adjustable



LCLR4W  
Silver  
Suitable for Cabinets



LCLR4W  
Black  
  
LCLR4W  
White



QS-105A



QS-104B



QS-101C



QS-101A

### SPECIFICATIONS

Code	TL002-3W	TL-D0307	TL-D302	LCLR4W	QS-105A	QS-104B	QS-101C	QS-101A
Colour temp	2700/3000K	3000K	3000K	2800-3000K / 6000-6500k	2800-3000K / 6000-6500k			3000K
Lumens	150	200	200	100-120(DL)/80-90(WW)	140 (W)/120 (WW)	150 (W)/120 (WW)	140 (W)/120 (WW)	180
Beam Angle	38°	45°	30°/45°/60°	120°	30°/45°	120°	30°/45°	15°/45°
Watts	3W	3W	3W	1 x 4W	3	3	3	3
Dimensions	Ø35mm x 49mm	Ø45mm x 32mm	Ø51mm x 32mm	Ø69mm x 12mm	Ø50mm x 32mm	Ø50mm x 25mm	Ø50.5mm x 35mm	Ø53mm x 53mm
Cut out	Ø26mm	Ø38mm	Ø42mm	Ø55mm	Ø42mm	Ø41mm	Ø37mm	Ø46mm
Chip	CREE	EPISTAR	CREE	CREE XRE P4 LED	CREE LED	CREE LED	CREE LED	CREE LED
Voltage	9V	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	700 mA
Life Span	±50,000 hours	±50,000 hours	±50,000 hours	±50,000 hours	±50,000 hours	±50,000 hours	±50,000 hours	±50,000 hours