# LED Recessed downlight

- Dimmable via a Cbus interface or simple pot dimmer
- Remote driver
- Two sizes: Ø 180mm x 13mm or Ø 240mm x 13mm
- Available in both Cool White and Warm White
- 48 hours aging test
- Low working temperature, long working lifetime
- Can be ceiling or wall surface-mounted, recessed mounted

| SPECIFICATIONS | | | | |
|---|---|---|---|---|
| Product Code | LDLF7W24VCW | LDLF7W24VWW | LDLF14W24VCW | LDLF14W24VCW |
| Operational voltage | Low voltage 24VDC | | | |
| Colour temperature | Cool white 6500k | Warm white 3200k | Cool white 6500k | Warm white 3200k |
| Lumens | 590 | 500 | 1040 | 980 |
| Wattage | 7 | 7 | 14 | 14 |
| Light source | SMD LEDs on edge of plate | | | |
| Uniformity of light colour | >90% | | | |
| Colour rendering index (Ra) | >85 | | | |
| Lifespan | > 50,000 hours (approx 8 years) | | | |
| Beam angle | 120˚ | | | |
| Dimensions | 180mm diam. x 13mm | 180mm diam. x 13mm | 240mm diam. x 13mm | 240mm diam. x 13mm |
| Cut out required | 160mm | 160mm | 220mm | 220mm |
| Ambient temperature | -40˚C to 60˚C | | | |
| Working temperature | 33˚C to 55˚C at room temperature | | | |

www.tec-ledlighting.com.au

**TEC-led lighting Pty Ltd**
Unit 9 / 7-9 Kent Road, Mascot NSW 2020
Telephone: (02) 9317 4177 Facsimile: (02) 9317 3544
Email: sales@tec-ledlighting.com.au